



Emergency Battery Backup

Sump Pump System

Link₂O™ Remote Monitoring

Constantly monitors system conditions, and alerts you (by cellphone or computer) when your basement is in danger of flooding. At home, at work, or across the globe – you are protected and informed.

Proprietary Smart Charging Technology

Recharges battery 25% faster and extends battery life.

High Performance Pump

Removes up to 83% more gallons per charge than the leading competitor.



LEARN MORE AT:
www.mylink2o.com



12V 2700 GPH FPDC30

PERFORMANCE (GPH)						SOLIDS HANDLING
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	14'	MAX. LIFT	
FPDC30	2700	2040	1260	360	15'	3/16"

FEATURE	FLOTEC® FPDC30	COMPETITION	FLOTEC ADVANTAGE
Max Flow (12.7V)	2700	2200	22% more flow
Flow @ 10' (12.7V)	1260	900	40% more flow
Max Head	15'	14'	7% higher head
Gallons per charge @ 10' head	11,500	6300	83% more gallons per charge
Charger	2.0 AMPS	1.6 AMPS	25% faster charging

*Performance data based on internal testing using BAT75

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FPDC30	2 YEAR	022315368385	18.25 x 10.13 x 16.63	20	12.2 LBS.



Includes: battery case control unit, 12V pump, reed switch, AC power supply, wireless gateway, 1-1/4" NPT to 1-1/2" glue PVC elbow

Compatible with flooded and sealed AGM deep cycle lead acid batteries.

For best performance use Flotec BAT40 or BAT75 sealed AGM batteries.

293 Wright Street, Delavan, WI 53115
For Questions or Installation Instructions:
www.flotecwater.com 1-800-365-6832