

## 2 HP SUBMERSIBLE SEWAGE GRINDER PUMP HWG(X) MODELS

R.P.M.	3450					
MOTOR TYPE	ENCLOSED, OIL COOLED INDUCTION					
MOTOR DESIGN NEMA TYPE	B (3ø) L (1ø)					
GENERAL INSULATION CLASS	F					
STATOR WINDING CLASS	F					
MAXIMUM STATOR TEMPERATURE	130°C					
MOTOR PROTECTION	BI-METALLIC, TEMPERATURE SENSITIVE DISC, SIZED TO OPEN AT 120°C AND AUTOMATICALLY RESET @ 30–35°C DIFFERENTIAL, ONE IN SINGLE PHASE, TWO IN THREE PHASE					
ELECTRICAL RATINGS	HEAT SENSOR	24VDC 5AMPS	115VAC 5AMPS	230VAC 5AMPS		
ELECTRICAL RATINGS	SEAL FAIL	L 300VAC 5mA				
VOLTAGE TOLERANCE	±10%					

MODEL CODE	HP	VOLTAGE	PHASE	NEC CODE LETTER	SERVICE FACTOR	FULL LOAD AMPS	START AMPS	FULL LOAD KW	START KVA
HWGX200BD		208	1	F	1.25	15	52.9	2.6	11.0
HWGX200DD		208 2 230	3			9.5	34.74	2.5	12.5
HWGX200CD	2		1			13.5	61.51	3	14.1
HWGX200ED		230				8.4	35.01	2.9	13.9
HWGX200FD	460	460	3			4.2	17.66	2.9	14.1
HWGX200GD		575				3.4	13.41	2.6	13.4

🚸 PENTAIR

1101 Myers Parkway Ashland, OH 44805 Ph: 855.274.8947



pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

©2023 Pentair. All Rights Reserved.