

SUBMERSIBLE SOLIDS HANDLING PUMPS

4SD(X) SERIES

RPM	3500			
MOTOR TYPE	PREMIUM EFFICIENT, IEC 60034 -30 LEVEL IE3			
MOTOR DESIGN NEMA TYPE	A or B (3Ø)			
GENERAL INSULATION CLASS	H			
STATOR WINDING CLASS	H			
MAXIMUM STATOR TEMPERATURE RATING	356°F (180°)			
MOTOR PROTECTION	3 PHASE, BI-METALLIC, TEMPERATURE SENSITIVE DISC, SIZED TO OPEN AT 130°C AND AUTOMATICALLY RESET @ 82°C DIFFERENTIAL			
ELECTRICAL RATINGS	HEAT SENSOR	24VDC 5 AMPS	115VAC 5AMPS	230VAC 5AMPS
	SEAL FAIL	300VAC 5mA		
VOLTAGE TOLERANCE	±10%			

HP	VOLTAGE	PHASE	NEC CODE	SF	FULL LOAD AMPS	SF AMPS	LOCKED ROTOR AMPS	RUN KW	START KVA	RUN KVA	MTR. EFFICIENCY @100% FL	PWR. FACT. @SF	PWR. FACT. @100% FL	PWR. FACT. @75% FL	PWR. FACT. @50% FL
25	230	3	G	1.15	77.8	90.0	386.0	28.1	153.6	31.0	91.7	90.2	91.5	92.0	92.0
	460				38.9	45.0	193.0	28.1	153.6	31.0	91.7	90.2	91.5	92.0	92.0
	575				31.1	36.0	143.0	28.1	142.2	30.9	91.7	90.2	91.5	92.0	92.0
30	460	3	J	1.15	41.0	48.1	290.0	39.2	230.8	32.6	91.7	91.5	92.0	90.8	90.6
	575				32.8	38.5	232.0	39.2	230.8	32.6	91.7	91.5	92.0	90.8	90.6
40	460	3	G	1.0	59.0	70.0	290.0	42.2	230.8	47.0	92.4	-	90.0	92.0	90.0
	575				47.2	56.0	232.0	42.2	230.8	47.0	92.4	-	90.0	92.0	90.0

1101 Myers Parkway
Ashland, OH 44805
Ph: 855.274.8947
Fx: 800.426.9446

490 Pinebush Rd., Unit 4
Cambridge, Ontario N1T 0A5, Canada
Ph: 800.363.7867
Fx: 888.606.5484

pentair.com/hydromatic